15CXN76 8 Ω

- 800 W continuous program power capacity
- 80° nominal coverage
- 40 - 18000 Hz response
- 99 dB sensitivity
- Single Neodymium magnet assembly
- Compatible with FB15CX40 crossover network





B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com

15CXN76 8 Ω

GENERAL

Nominal Diameter	**380 mm (15 in)**
Nominal Impedance	**8 Ω**
Frequency Range	**40 Hz - 18000 Hz**
Dispersion Angle Included by –6 dB down points.	**80 °**

PARAMETERS

Fs	**38 Hz**
Re	**5.1 Ω**
Qes	**0.3**
Qms	**5.8**
Qts	**0.28**
Vas	**246 dm³ (8.6 ft³)**
Sd	**855 cm² (132.5 in²)**
η0	**3.7 %**
Xvar	**6 mm**
Mms	**82 g**
Bl	**17.8 Tm**
Le	**0.9 mH**
EBP	**127 Hz**

SPECIFICATIONS HF UNIT

Nominal Diameter	**380 mm (15 in)**
Nominal Impedance	**8 Ω**
Minimum Impedance	**8 Ω**
Nominal Power Handling 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance. Loudspeaker in free air.	**80 W**
Continuous Power Handling Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	**160 W**
Sensitivity Applied RMS Voltage is set to 2.83V.	**105 dB**
Recommended Crossover 12 dB/oct. or higher slope high-pass filter.	**1.2 kHz**
Voice Coil Diameter	**75 mm (3 in)**
Winding Material	**Aluminium**
Inductance	**0.14 mH**
Flux Density	**1.9 T**
Diaphragm Material	**Polyester/Titanium**

SPECIFICATIONS LF UNIT

Nominal Diameter	**380 mm (15 in)**
Nominal Impedance	**8 Ω**
Minimum Impedance	**6 Ω**
Nominal Power Handling 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.	**400 W**
Continuous Power Handling Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	**800 W**
Sensitivity Applied RMS Voltage is set to 2.83V.	**99 dB**
Voice Coil Diameter	**76 mm (3 in)**
Winding Material	**Copper**
Former Material	**Glass Fibre**
Winding Depth	**16.5 mm (0.65 in)**
Magnetic Gap Depth	**8 mm (0.31 in)**
Flux Density	**1.15 T**
Woofer Cone Treatment	**WP Waterproof Front Side**

DESIGN

Magnet Material	**Neodymium Ring**
Woofer Cone Treatment	**WP Waterproof Front Side**

MOUNTING AND SHIPPING INFO


Overall Diameter	**393 mm (15.5 in)**
Bolt Circle Diameter	**374 mm (14.7 in)**
Baffle Cutout Diameter	**354 mm (13.94 in)**
Depth	**198 mm (7.8 in)**
Flange and Gasket Thickness	**16 mm (0.62 in)**
Net Weight	**5.4 kg (11.9 lb)**
Shipping Units	**1 pcs**
Shipping Weight	**7 kg (15.43 lb)**
Shipping Box	**500x495x275 mm (19.69x19.49x10.83 in)**


SERVICE KITS

HF replacement-diaphragm	**MMD9028M**
LF recone-kits	**RCK15CXN768**

B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com


15CXN76 8 Ω






B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com


15CXN76 8 Ω






B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com

15CXN76 8 Ω





Model:	**15 CXN 76**			
Enclosure Type:	**Bass Reflex**			
Internal Net Volume (Liters):	**100**			
Tuning Frequency (Hz):	**50**	Port Area (cm²):	**169,8**	
Frequency (-3 dB) (Hz):	**55,7**	Port Length (cm):	**7,5**	
Excursion Limited Maximum SPL at 1 meter (dB):	**121,3**	equal to	**214,5** Watts	(Bass Band Power Rating)
Thermal Limited Maximum SPL at 1 meter (dB):	**124,0**	equal to	**400,0** Watts	(Mid Band Power Rating)

B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com

15CXN76 8 Ω

