DE52 8 Ω

SPECIFICATIONS

Driver mounted on B&C ME90 horn

Throat Diameter	**36 mm (1.4 in)**
Nominal Impedance	**8 Ω**
Minimum Impedance	**8.2 Ω**
Nominal Power Handling 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.	**70 W**
Continuous Power Handling Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	**140 W**
Sensitivity Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.	**108 dB**
Frequency Range	**1 kHz - 17 kHz**
Recommended Crossover 12 dB/oct. or higher slope high-pass filter.	**1 kHz**
Voice Coil Diameter	**51 mm (2 in)**
Winding Material	**Aluminium**
Inductance	**0.14 mH**
Flux Density	**1.8 T**
Diaphragm Material	**HT Polymer**

MOUNTING AND SHIPPING INFO

Four M6 holes 180° on 76 mm (3 in) diameter

Overall Diameter	**134 mm (5.28 in)**
Depth	**60 mm (2.36 in)**
Net Weight	**2.8 kg (6.17 lb)**
Shipping Units	**1 pcs**
Shipping Weight	**2.84 kg (6.25 lb)**
Shipping Box	**135x135x65 mm (5.31x5.31x2.56 in)**

SERVICE KITS


HF replacement-diaphragm	**MMD5508**


- 140 W continuous program power capacity
- 1.4" horn throat diameter
- 51 mm (2 in) aluminium voice coil
- HT Polymer diaphragm
- 1000 - 17000 Hz response
- 108 dB sensitivity




B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com

DE52 8 Ω


+120
+115
+110
+105
+100
+95
+90
+85
+80
+75
+70
dB SPL
20
50
100
200
500
1k
2k
5k
10k
20k
Hz


200
100
50
20
10
5
2
OHM
20
50
100
200
500
1k
2k
5k
10k
20k
Hz

DE52 8 Ω



B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com