beyma

PROFESSIONAL LOUDSPEAKERS
www.beyma.com


CD-10Nd/N

COMPRESSION DRIVER

KEY FEATURES

- 1” (25,4 mm) high frequency compression driver
- High sensitivity: 111 dB (1W / 1m)
- Ultra lightweight edgewound aluminium ribbon voice coil
- Aluminium cover
- Neodymium magnet
- Improved moving assembly mechanical coupling for excellent power handling capabilities
- PM-4 polymer diaphragm with higher surface tension energy





TECHNICAL SPECIFICATIONS

Nominal diameter	25,4 mm	1 in
Rated impedance		8 Ω
Minimum impedance		5,3 Ω
D.C. resistance		4,3 Ω
Power capacity [1]	70 W_{AES} above 1,2 kHz	
Program power [2]	140 W above 1,2 kHz	
Sensitivity [3]	111 dB 1W / 1m @ Z_N coupled to TD-164	

Frequency range		0,7 - 19 kHz
Recommended crossover		1,2 kHz or higher (12 dB/oct min.)
Voice coil diameter	44,4 mm	1,75 in
Magnetic assembly weight	1,1 kg	2,4 lb
Flux density		2,2 T
Bl factor		8,9 N/A

Notes:

[1] The power capaticty is determined according to AES2-1984 (r2003) standard.

[2] Program power is defined as the transducer’s ability to handle normal music program material.

[3] Sensitivity was measured at 1m distance, on axis, with 1W input, averaged in the range 1 - 7 kHz


beyma

PROFESSIONAL LOUDSPEAKERS

www.beyma.com

CD-10Nd/N

COMPRESSION DRIVER



Note: On axis frequency response measured coupled to TD-164 horn in anechoic chamber, 1W / 1m

MOUNTING INFORMATION

Overall diameter	100 mm	3,9 in
Depth	66 mm	2,6 in
Mounting	Three M5 threaded holes, 120º apart on 57 mm (2,24 in) diameter circle Two M5 threaded holes, 180º apart on 76,2 mm (3 in) diameter circle	
Net weight	1,2 kg	2,6 lb
Shipping weight	1,3 kg	2,9 lb

DIMENSION DRAWING

