PROFESSIONAL LOUDSPEAKERS

4FE32

4" - 30 W - 91 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	100 mm (4 in)
Overall Diameter	129.85/100.5 mm (5.11/3.96 in)
Bolt Circle Diameter	115.26 mm (4.54 in)
Baffle Cutout Diameter	91.5 mm (3.60 in)
Depth	49.8 mm (1.96 in)
Flange and Gasket Thickness	7.2 mm (0.28 in)
Net Weight	**270 g (0.6 lb)**
Shipping Box (Single Carton Box - 8 units)	225 x 225 x 150 mm (8.9 x 8.9 x 5.9 in)
Shipping Weight (8 units)	2.8 kg (6.2 lb)

PART NUMBER

Faston Terminals - 8 Ohm Version	01004084

NOTES:

Packaged and sold in multiples of 8 units

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.

(3) NBR (Rubber)

(4) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)


(5) Maximum excursion before permanent damage


TECHNICAL PARAMETERS


Nominal Impedance	8 Ohm
Minimum Impedance	7 Ohm
AES Power Handling **(1)**	30 W
Maximum Power Handling (2)	**60 W**
Sensitivity (1W/1m)	**91 dB**
Frequency Range	90÷20000 Hz
Voice Coil Diameter	**19 mm (0.75 in)**
Winding Material	Al
Former Material	Kapton
Winding Depth	6.8 mm (0.27 in)
Magnetic Gap Depth	**4 mm (0.16 in)**
Flux Density	1.4 T
Magnet	Neodymium Ring
Basket Material	Steel
Demodulation	No
Cone Surround **(3)**	Half Roll
NET Air Volume filled by Loudspeaker	0.075 dm^3 (0.003 ft^3)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	100 Hz
Re	6.5 Ohm
Qes	0.70
Qms	4.9
Qts	0.61
Vas	2.3 dm^3 (0.08 ft^3)
Sd	51.9 cm^2 (8.04 in^2)
Xmax **(4)**	2.73 mm
Xdamage **(5)**	6.8 mm
Mms	4.2 g
Bl	4.8 N/A
Le	0.18 mH
Mmd	3.8 g
Cms	0.60 mm/N
Rms	0.5 kg/s
Eta Zero	0.30 %
EBP	143 Hz







©Copyright 2026 **Faital S.p.A.** • All rights reserved.