faital PRO PROFESSIONAL LOUDSPEAKERS

5FE120

5" - 80 W - 88 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	130 mm (5 in)
Overall Diameter	144.8/124.5 mm (5.7/4.9 in)
Bolt Circle Diameter	133 mm (5.24 in)
Baffle Cutout Diameter	114 mm (4.49 in)
Depth	71.5 mm (2.81 in)
Flange and Gasket Thickness	6.5 mm (0.25 in)
Net Weight	**1.1 kg (2.5 lb)**
Shipping Box (Single Carton Box - 8 units)	302 x 275 x 186 mm (11.9 x 10.8 x 7.3 in)
Shipping Weight (8 units)	9.6 kg (21.2 lb)

PART NUMBER

Faston Terminals - 8 Ohm Version	01303979

NOTES:

Packaged and sold in multiples of 8 units

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.

(3) NBR (Rubber)

(4) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)


(5) Maximum excursion before permanent damage


TECHNICAL PARAMETERS


Nominal Impedance	8 Ohm
Minimum Impedance	6.2 Ohm
AES Power Handling **(1)**	80 W
Maximum Power Handling (2)	**160 W**
Sensitivity (1W/1m)	**88 dB**
Frequency Range	63÷6300 Hz
Voice Coil Diameter	**32 mm (1.26 in)**
Winding Material	Cu
Former Material	Kapton
Winding Depth	12.5 mm (0.49 in)
Magnetic Gap Depth	**6 mm (0.24 in)**
Flux Density	1 T
Magnet	Ferrite Ring
Basket Material	Steel
Demodulation	Aluminum Ring
Cone Surround **(3)**	Half Roll
NET Air Volume filled by Loudspeaker	0.3 dm^3 (0.011 ft^3)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	65 Hz
Re	5.4 Ohm
Qes	0.51
Qms	7.4
Qts	0.48
Vas	5.4 dm^3 (0.19 ft^3)
Sd	84 cm^2 (13.07 in^2)
Xmax **(4)**	5.25 mm
Xdamage **(5)**	9.5 mm
Mms	11.0 g
Bl	6.9 N/A
Le	0.41 mH
Mmd	10.1 g
Cms	0.55 mm/N
Rms	0.6 kg/s
Eta Zero	0.28 %
EBP	127 Hz







©Copyright 2026 **Faital S.p.A.** • All rights reserved.