
PROFESSIONAL LOUDSPEAKERS

HF201

2" - 100 W - 108 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Throat Diameter	50.8 mm (2 in)
Overall Diameter	170 mm (6.69 in)
90° Mounting Holes Diameter (4xM6)	102 mm (4.02 in)
Depth	66 mm (2.60 in)
Net Weight	**4.6 kg (10.2 lb)**
Shipping Box (Single carton box)	195 x 195 x 141 mm (7.7 x 7.7 x 5.6 in)
Shipping Weight	4.8 kg (10.6 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	00744169
Recone Kit - 8 Ohm Version	R0743887

NOTES:

Driver mounted on a **2" 90° x 40° Horn**

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.


(3) 12 dB/oct or higher slope high-pass filter


(4) Averaged within the frequency range


(5) The phase plug is recessed from the driver's exit which is at the end of a conical adaptation horn.

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7.2 Ohm
AES Power above 0.9 kHz (1)	**100 W**
AES Power above 0.65 kHz	50 W
Maximum Power above 0.9 kHz (2)	**200 W**
Maximum Power above 0.65 kHz	100 W
Minimum Crossover Frequency **(3)**	0.9 kHz
Sensitivity (1W/1m) (4)	**108 dB**
Frequency Range	0.5÷18 kHz
Voice Coil Diameter	**74 mm (2.91 in)**
Winding Material	**Al**
Former Material	Kapton
Diaphragm Material	**Titanium**
Diaphragm Shape	Dome
Winding Depth	2.35 mm (0.09 in)
Magnetic Gap Depth	3.2 mm (0.13 in)
Flux Density	1.7 T
Magnet	Ferrite Ring
Re	5.6 Ohm
Phase Plug Design	Annular
Exit Angle **(5)**	36° Conical
NET Air Volume filled by HF Driver	1.05 dm^3 (0.037 ft^3)







©Copyright 2026 **Faital S.p.A.** • All rights reserved.