# Pro SoundBar PSB-2

2.0 Channel Commercial Soundbar

## Key Features:

- Full-range stereo sound without the need for a subwoofer
- Application-specific features for guestrooms and staterooms
- Simplified HDMI input & CEC control
- Effortless Bluetooth connectivity and control
- Neutral room décor aesthetic
- Volume limiting
- Lockout plate prevents tampering
- Internal, universal power supply for global installations, no “wall worts”
- Securely mounts to wall/table to prevent theft or drifting on cruise ships
- Mounting hardware, power and HDMI cable
- Auto standby for reduced energy usage
- Non-absorbent materials for easy cleaning



## Applications:

- Hotel guestrooms
- Cruise ship staterooms
- Meeting rooms and education spaces

The PSB-2 high-fidelity, professional active soundbar is designed specifically for use in hotel guestrooms and cruise ship staterooms. Targeting these unique applications, the JBL Pro SoundBar PSB-2 reduces the cost and complexity found in consumer-grade soundbars while providing excellent sound quality, security, and reliability.

The all-in-one design provides full-range sound without the need for a separate subwoofer and a volume limiting switch to control maximum volume output.

The PSB-2 has HDMI and Bluetooth digital inputs are included and a single source control button on top of the speaker makes switching between sources simple. Automatic Bluetooth pairing management and the ability to update the Bluetooth name of each PSB-2 can be helpful when managing multiple PSB-2s.

## Specifications:

| System: | |
|---|---|
| Frequency Range (-10dB): | 62Hz – 20kHz |
| Frequency Response (+/-3dB): | 100Hz – 20kHz |
| Maximum Peak SPL: | 101 dB-SPL at 1m* |
| Input Connectors: | HDMI Input (HDMI 2.1), HDMI Output/ARC (HDMI 2.1) |
| Bluetooth: | 5.3 |
| Nominal Input Sensitivity: | -8dBFS for 93 dB-SPL at 1m (Max Volume setting) |
| HF Driver: | 2 x 19 mm (0.75") Soft Dome Tweeter (one per channel) |
| LF Driver: | 4 x 51 mm (2.0") Low-Frequency Driver (two per channel) |
| Power Amp: | 20W per Channel, Class D |
| Enclosure Material: | Injection-Molded ABS + PC |
| Enclosure Finish: | Black |
| Mounting/Installation: | Two included brackets, desk/table or on-wall mounting. See Owner's Manual for installation diagrams. |
| AC Power: | Input: 100-240 VAC, 50/60 Hz, 1.0 A |
| **Sleep Mode Power:** | When the HDMI ports are disconnected, the sleep mode power is < 0.5W; When one of the HDMI port is connected, the sleep mode power is < 2W. |
| Dimensions (H x W x D): | 90 x 900 x 65 mm (3.54 x 35.4 x 2.55 in). See Owner's Manual for dimensional drawing. |
| Weight: | 1.8kg (4.0lbs) |
| Shipping Weight: | 2.5kg (5.5lbs) |
| Included Accessories: | See Owner's Manual |

*Full Bandwidth Pink Noise Measured C-unweighted

**JBL Professional** 8500 Balboa Blvd. Northridge, CA 91325 USA

© 2024 HARMAN International Industries, Incorporated. All rights reserved.

08/2024