EVOX J9

ACTIVE THREE-WAY PORTABLE COLUMN SPEAKER



Description

EVOX J9 is an active, three-way portable column system designed for maximum clarity and power in a compact format. A 1.75” compression driver coupled with a 120° × 40° True Resistive Waveguide ensures wide, consistent coverage, while 6 x3” full-range transducers and a high-power 12” woofer in a bass-reflex enclosure deliver articulate mids and deep, controlled lows. Driven by a 2100W onboard dual-channel Class-D amplifier, EVOX J9 delivers an impressive 130 dB Max SPL output. Part of the EVOX J Series, it incorporates RCF’s tour-grade technology into a sleek, unobtrusive package that delivers crystal-clear vocals, natural musical response, and effortless deployment for bands, DJs, and live performers.

Features

› 130 dB Max SPL
› 2100 W Class-D Amplifier - Built-In DSP
› 1.75” Neo Compression Driver - 120° X 40° True Resistive Waveguide
› 6 × 3” Full-Range Neo Transducers
› 12” High-Power Woofer
› Enhanced Coverage And Clarity
› Composite Cabinet With Aluminum Stand Mount
› Sleek, Road-Ready Design
› Top Speaker Padded Carrying Bag Included
› J9 Sub: 20,2 kg - 44.53 lb / J9 Top: 5.8 kg - 12.78 lb

Part Number


13000928	EVOX J9	220-240 V	Black	EAN 8024530024123
13000929	EVOX J9	100-120 V	Black	EAN 8024530024161
13000983	EVOX J9 W	220-240 V	White - RAL 9003	EAN 8024530024437
13000984	EVOX J9 W	100-120 V	White - RAL 9003	EAN 8024530024468

Products are continually improved. All specifications are therefore subject to change without notice.

Line Art 2D

EVOX J9

ACTIVE THREE-WAY PORTABLE COLUMN SPEAKER



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response	40 Hz - 20000 Hz
	Max SPL @ 1m	130 dB
	Horizontal coverage angle	120°
	Vertical coverage angle	40°
Transducers	Compression Driver	1 x 0.75'' neo, 1.75'' v.c
	Fullrange	6 x 3.0'' neo, 1.0'' v.c
	Woofer	1 x 12'', 2.5'' v.c
Input/Output section	Input signal	bal/unbal
	Input connectors	Combo XLR/Jack
	Output connectors	XLR
	Input sensitivity	-2 dBu/+4 dBu
Processor section	Crossover Frequencies	200 Hz/1800 Hz
	Protections	Thermal, RMS
	Limiter	Soft Limiter
	Controls	Volume, Presets: LINEAR/LIVE, CLUB, VOICE
Power section	Total Power	2100 W Peak
	High frequencies	700 W Peak
	Low frequencies	1400 W Peak
	Cooling	Convection
	Connections	VDE
Standard compliance	Safety agency	CE compliant

EVOX J9

ACTIVE THREE-WAY PORTABLE COLUMN SPEAKER

Physical specifications	Cabinet/Case Material	PP Composite
	Handles	1 Top
	Pole mount/Cap	Quick-fit socket
	Grille	Steel
	Color	Black, White - RAL 9003
Size / Weight	Height	2080.1 mm / 81.89 inches
	Width	350 mm / 13.78 inches
	Depth	462.6 mm / 18.21 inches
	Weight	26 kg / 57.32 lbs

ACCESSORIES

Rigging / Mounting

FLOOR STANDS

13360768	PMK60768	Black - RAL 9005	EAN 8024530025083
13360770	PMK60770	White - RAL 9003	EAN 8024530025090

Protections

COVERS

13360751	CVR60751	Black	EAN 8024530024536
13360752	CVR60752	Black	EAN 8024530024543