MB15N405

MID - BASS



Description

The MB15N405 is a hypervented neo mid-bass design with a linear frequency response and very high efficiency. To get this performance the magnetic structure use a high flux neo disc and the cone assembly a fibre loaded exponential shape along with a high excursion triple roll, constant geometry surround. The fibreglass former and aluminium voice coil provide a very high power handling maintaining a light mass and a proper Q factor for bass alignment.

Features

- 4-inch, fiberglass inside/outside copper voice coil
- 2200W continuous program power handling
- 100 dB Sensitivity
- 45 Hz – 2.5 kHz Frequency range
- Dual-forced air ventilation for minimum power compression
- Triple roll surround and exponential cone geometry

Part Number

11100108	MB15N405	8ohm

MB15N405

MID - BASS

TECHNICAL SPECIFICATIONS

General specifications	Nominal Diameter	15 inch / 381 mm
	Rated Impedance	8 ohm
	Program Power (watt)	2200 W
	Power handling capacity	1100 W
	Sensitivity	100.0 dB
	Frequency range	45 - 2500 Hz
	Effective piston diameter	340 mm / 13.39 inch
	Max. Excursion Before Damage	53 mm / 2.09 inch
	Minimum Impedance (ohm)	5.9 ohm
	Voice Coil Diameter	4.0 inch / 102 mm
	Voice Coil Winding Material	Aluminum
	Voice Coil Length	20 mm / 0.79 inch
	Number of layers	2
	Kind of layers	inside/outside
	Top Plate Thickness	12 mm / 0.47 inch
	Cone Design	Curved
	Surround Material	Polycotton
	Surround Design	Triple roll
	Magnets	Neodymium
	Hypervented magnetic structure	Yes
	Spider	Single
Thiele - small parameters	Resonance frequency (Fs)	46 Hz
	DC resistance (Re) (ohm)	5.50 ohm
	Mechanical factor	4.80 Qms
	Electrical factor	0.28 Qes
	Total factor	0.27 Qts
	Bl factor (Bl) (T x m)	23.50 T x m
	Effective moving mass (Mms)	98.0 g
	Equivalent Cas air loaded (Vas)	124.0 liters
	Effective piston area (Sd)	0.090 m2
	Max. linear excursion (Xmax)	7 mm
	Voice coil inductance @ 1kHz (Le1k)	1.10 mH
	Half-space efficency (Eff)	4.10%
Mounting information	Overall diameter	393 mm / 15.47 inches
	Bolt circle diameter	371-376 mm / 14.61-14.8 inch
	Bolt hole diameter	7 mm / 0.28 inch
	Front mount baffle cut-out	354 mm / 13.94 inch
	Rear mount baffle cut-out	354 mm / 13.94 inch
	Volume occupied by the driver	3.8 liters / 0.15 ft3
Standard compliance	Safety agency	CE compliant

MB15N405

MID - BASS

Size / Weight	Height	160 mm / 6.3 inches
	Diameter	393 mm / 15.47 inches
	Weight	8.6 kg / 18.96 lbs

MB15N405

MID - BASS

Line Art 2D



